



**Application** : For water, sewage and neutral liquids to max. 70° C.

**Range** : DN 50-600

**Flanges** : BS4504 PN16

**Pressure Class** : PN10 - 25

**Applied Pressure** : Max 25 bar

**Coating** : Fusion Bonded Epoxy Paint (Min. 250 microns DFT)

### Properties

- Produced by casting with three flanges full stud.
- Easy installation or dismantling and compensates the axial movement of equipments like valves, flow meter, pump etc...

### SPECIFICATIONS

No	Part	Material Description
1	Flanged Body	Ductile Iron, BS EN 1563 Grade 500/7
2	Gland Ring	Ductile Iron, BS EN 1563 Grade 500/7
3	Stud	Stainless Steel / Galvanized Steel
4	Tie Bolt	Stainless Steel / Galvanized Steel
5	Washer	Stainless Steel / Galvanized Steel
6	Nut	Stainless Steel / Galvanized Steel
7	Rubber Seal	EPDM, ASTM D 70° - 80° IRHD



### Sales Office :

**TEK VALVE (M) SDN. BHD.** (Company No : 524990-A)

PT 22432, Lot Asal 6535, Sungai Puloh, Batu 5 1/2,  
Jalan Kapar, 42450 Klang, Selangor Darul Ehsan.

Tel : (006) 03-3291 3963

Fax:(006) 03-3290 5126

E-mail: tekvalve@yahoo.com